

Progress towards a new international standard for storing nuclear data

CSEWG 2016

Caleb Mattoon

November 15, 2016



Motivation: the ENDF-6 format is having trouble keeping up with expanding needs of nuclear data users.

- For over 50 years, ENDF-6 has been the standard for storing and exchanging nuclear data
 - Originally neutrons only, has since expanded to handle other particles.
 - Format gradually modified to support double-differential distributions, covariances, more types of reactions, etc.
 - Data are computer-readable... except when they aren't!
 - Format limitations sometimes force evaluators to use non-standard data representations like the 'LIP' product modifier flag: “The exact meaning assigned to LIP should be explained in the File 1, MT=451 comments”
 - Despite format checking codes, bugs in ENDF-6 evaluations remain difficult to find and fix!
- New generation of nuclear data experts asks for modern tools to handle data!

LLNL has made an initial attempt at a new format, which can be downloaded at <https://ndclx4.bnl.gov/gf/project/gnd/>

- Sub-group participants will
 - Develop a common data model for reaction data
 - Agree on best practices and how to “enforce” them
 - Test things out with their local ENDF-formatted databases
 - Propose a process for dissemination and future modifications
- LLNL and USNDP is committed to seeing this through
- Benefits are significant
 - Attract and retain next generation of scientists and engineers
 - Leverage significant infrastructure that will continue to evolve
 - Overcomes limitations of existing format in an extensible way
 - Positions community to link disparate data products to each other

WPEC subgroup #38 was approved in May 2012, and has since met seven times (plus multiple phone conferences)

- Meetings mainly held at the NEA (Paris), but also at JAEA, BNL, IAEA and OECD
- Contributors from all data projects joined in the discussions.



SG38 work was divided into several sub-tasks:

- Low-level data containers
 - Similar to ENDF LIST, TAB1, TAB2, etc.
 - Work with other data projects (e.g., ENSDF, EXFOR, RIPL)
- Hierarchy for storing particle data and nuclear level schemes and decay data
- Top-level hierarchy for storing nuclear reaction data
- Infrastructure for data handling, processing, plotting, etc.
- API for reading and writing data in the new structure
- Defining the tests that will be needed to assure quality of data
- Documentation and governance

SG38 work was divided into several sub-tasks:

- Low-level data containers
 - Similar to ENDF LIST, TAB1, TAB2, etc.
 - Work with other data projects (e.g., ENSDF, EXFOR, RIPL)
- Hierarchy for storing particle data and nuclear level schemes and decay data
- Top-level hierarchy for storing nuclear reaction data
- Infrastructure for data handling, processing, plotting, etc.
- API for reading and writing data in the new structure
- Defining the tests that will be needed to assure quality of data
- Documentation and governance

Nearly
complete

Continued
in SG43

SG-B is being revived to
provide long-term governance

SG38 will be completed with the publication of 4 'requirements and specifications' documents

General-Purpose Data Containers for Science and Engineering*

OECD/NEA/WPEC Subgroup 38

May 4, 2015

Basic Data Containers, 60 pages

Requirements and specifications for a particle database

WPEC Subgroup 38

September 14, 2016

Contents

- 1 Introduction
- 2 Definitions
- 3 Requirements
 - 3.1 Discussion
- 4 Specifications overview
- 5 Particle naming schemes
 - 5.1 Specification
- 6 Physical quantities
 - 6.1 double
 - 6.1.1 Specifications
 - 6.2 integer
 - 6.3 floating
 - 6.4 string
- 7 Uncertainties
 - 7.1 uncertainty
 - 7.1.1 Spec
 - 7.2 confidence
 - 7.2.1 Spec
 - 7.3 interval
 - 7.3.1 Spec
 - 7.4 cell

Particle database

Particle
database,
31 pages

BROOKHAVEN
NATIONAL LABORATORY

BNL-112394-2016-IE

Detailed requirements for a next generation nuclear data structure

David Brown

OECD/NEA/WPEC SubGroup 38

July 05, 2016

National Nuclear Data Center
Brookhaven National Laboratory
P.O. Box 5000
Upton, NY 11973-5000
www.nndc.bnl.gov

U.S. Department of Energy
Office of Science, Office of Nuclear Physics

Notice: This manuscript has been authored by employees of Brookhaven Science Associates, LLC under Contract No. DE-SC0012704 with the U.S. Department of Energy. The publisher by accepting the manuscript for publication acknowledges that the United States Government retains a non-exclusive, paid-up, irrevocable, world-wide license to publish or reproduce the published form of this manuscript, or allow other to do so, for United States Government purposes.

Specifications for the next generation nuclear data hierarchy

WPEC Subgroup 38

September 10, 2016

[illegible]

Top-level hierarchy requirements (109 pages) and specifications (61 pages)

- All available at <https://www.oecd-nea.org/science/wpec/sg38/>

Brief overview of some SG38 specifications: basic data containers

- 1-d functions (such as cross section and nubar) are stored as a list of (x,y) pairs with interpolation:

```
<XYs1d label="eval" style="eval" interpolation="lin-lin">
- <axes>
  <axis label="energy_in" unit="eV"/>
  <axis label="crossSection" unit="b"/>
</axes>
- <values length="164">
  128262 0 1.3e5 0.0615264 1.4e5 0.225903 1.5e5 0.322846 2e5 0.561636 ... 5.5e7 7.56553e-3 6e7 6.81747e-3
</values>
+ <uncertainties></uncertainties>
</XYs1d>
```

- Changing interpolations are handled with a 'regions' container:

```
<regions1d label="eval" style="eval">
- <axes>
  <axis label="energy_in" unit="eV"/>
  <axis label="crossSection" unit="b"/>
</axes>
+ <XYs1d interpolation="log-log"></XYs1d>
+ <XYs1d interpolation="lin-lin"></XYs1d>
+ <uncertainties></uncertainties>
</regions1d>
```


Brief overview of some SG38 specifications: basic data containers

- 2-d functions (i.e. outgoing energy distributions) are similar to TAB2, composed of 1-d functions along with an interpolation rule:

```
<XYs2d interpolation="lin-lin" interpolationQualifier="unitbase">
- <axes>
  <axis label="energy_in" unit="eV"/>
  <axis label="energy_out" unit="eV"/>
  <axis label="P(energy_out|energy_in)" unit="1/eV"/>
</axes>
+ <XYs1d value="2969996.0" interpolation="lin-lin"></XYs1d>
+ <XYs1d value="3000000.0" interpolation="lin-lin"></XYs1d>
...
+ <XYs1d value="55000000.0" interpolation="lin-lin"></XYs1d>
+ <XYs1d value="60000000.0" interpolation="lin-lin"></XYs1d>
</XYs2d>
```

- Other data containers include series (i.e. Legendre expansions and other polynomials), multi-dimensional arrays, 'gridded' arrays (used to store covariances and transfer matrices), and tables (for resonance parameters)

Brief overview of SG38 specifications: overall organization of data

- GND 'reactionSuite' is similar to ENDF-6 'MAT'. Data inside the reactionSuite are organized in a nested hierarchy

```
- <reactionSuite projectile="n" target="Mn55" version="GND 1.7" projectileFrame="lab">  
  + <styles></styles>  
  + <documentations></documentations>  
  + <aliases></aliases>  
  + <particles></particles>  
  + <resonances reconstructCrossSection="true"></resonances>  
  + <reactions></reactions>  
  + <sums></sums>  
  + <productions></productions>  
</reactionSuite>
```

Brief overview of SG38 specifications: overall organization of data

- Largest section is <reactions>, containing the list of all reactions that sum to total:

<reactions>

```
+ <reaction label="0" outputChannel="n + Mn55" date="2011-02-01" ENDF_MT="2"></reaction>
+ <reaction label="1" outputChannel="n + Mn55_e1" date="2011-02-01" ENDF_MT="51"></reaction>
+ <reaction label="2" outputChannel="n + Mn55_e2" date="2011-02-01" ENDF_MT="52"></reaction>
+ <reaction label="3" outputChannel="n + Mn55_e3" date="2011-02-01" ENDF_MT="53"></reaction>
+ <reaction label="4" outputChannel="n + Mn55_e4" date="2011-02-01" ENDF_MT="54"></reaction>
+ <reaction label="5" outputChannel="n + Mn55_e5" date="2011-02-01" ENDF_MT="55"></reaction>
+ <reaction label="6" outputChannel="n + Mn55_e6" date="2011-02-01" ENDF_MT="56"></reaction>
+ <reaction label="7" outputChannel="n + Mn55_e7" date="2011-02-01" ENDF_MT="57"></reaction>
+ <reaction label="8" outputChannel="n + Mn55_e8" date="2011-02-01" ENDF_MT="58"></reaction>
+ <reaction label="9" outputChannel="n + Mn55_e9" date="2011-02-01" ENDF_MT="59"></reaction>
```

...

Brief overview of SG38 specifications: contents of a 'reaction'

- Each reaction stores a cross section and an outputChannel (with a Q-value and a list of products):

```
<reactions>
- <reaction label="0" outputChannel="n + Mn55" date="2011-02-01" ENDF_MT="2">
  + <crossSection></crossSection>
  - <outputChannel genre="twoBody">
    + <Q></Q>
    - <products>
      - <product name="n" label="n">
        + <multiplicity></multiplicity>
        + <distribution></distribution>
      </product>
      - <product name="Mn55" label="Mn55" ENDFconversionFlag="implicitProduct">
        + <multiplicity></multiplicity>
        + <distribution></distribution>
      </product>
    </products>
  </outputChannel>
</reaction>
+ <reaction label="1" outputChannel="n + Mn55_e1" date="2011-02-01" ENDF_MT="51"></reaction>
...
```

Brief overview of SG38 specifications: using 'styles' to store more than one type of data

- GND can store various types of processed data along with evaluated data. 'styles' section has a directory of data types:

```
<styles>
+ <evaluated label="eval" date="2011-02-01" library="ENDF/B" version="8.0.2"></evaluated>
  <crossSectionReconstructed label="recon" derivedFrom="eval" date="2016-09-14"/>
- <heated label="h1" derivedFrom="eval" date="2016-09-14">
  <temperature value="3.e2" unit="K"/>
</heated>
- <heated label="h2" derivedFrom="eval" date="2016-09-14">
  <temperature value="1.2e3" unit="K"/>
</heated>
</styles>
```

- Each data style may appear inside crossSection, multiplicity, distribution, etc.

```
<crossSection>
+ <resonancesWithBackground label="eval" style="eval"></resonancesWithBackground>
+ <XYs1d label="recon" style="recon"></XYs1d>
+ <XYs1d label="h1" style="h1" accuracy="0.002"></XYs1d>
+ <XYs1d label="h2" style="h2" accuracy="0.002"></XYs1d>
</crossSection>
```


SG38 work will continue with new subgroup #43 and long-term subgroup B:

- Low-level data containers
 - Similar to ENDF LIST, TAB1, TAB2, etc.
 - Work with other data projects (e.g., ENSDF, EXFOR, RIPL)
- Hierarchy for storing particle data and nuclear level schemes and decay data
- Top-level hierarchy for storing nuclear reaction data
- Infrastructure for data handling, processing, plotting, etc.
- API for reading and writing data in the new structure
- Defining the tests that will be needed to assure quality of data
- Documentation and governance

Nearly
complete

Continued
in SG43

SG-B is being revived to
provide long-term governance

New subgroups will officially start in May 2017. Now working to define their goals and scope:

■ SG-B

- From proposal: “... propose that a new WPEC long-term subgroup become the stewards of a new international standard for a modern nuclear database structure.”
 - Endorse, promote and maintain the new format. Includes facilitating training and education for evaluators, and approving and adopting future changes.

■ SG43

- Provides infrastructure to accompany the new format. Main goals:
 - Design and implement an API to read and write GND-formatted files
 - Define a list of tests (including data format tests and physics tests) that need to be implemented for data quality assurance.

SG-38 produced a format specification, now focus turns to disseminating the format and building infrastructure.

- SG-38 requirements and specifications documents under final revision, will be published soon
- SG-B takes on format governance
- SG-43 expands the infrastructure for generating, checking, manipulating and using GND-formatted data

